

# Moro

— OXIDE



1000x3000 mm / 47.2"x118.1"



1000x3000 mm Laminam 3+ | Laminam 5  
1000x1000 mm Laminam 5  
1000x3000 mm ♦ Laminam 3

## Coefficient of friction: Laminam 5 / Laminam 5+

*Coefficiente d'attrito | Coefficient de frottement | Reibungskoeffizient | Coeficiente de fricción |*

Norm-Method	1000x3000 mm
<i>Norma-Metodo   Norme-Méthode   Norm-Methode   Norma-Metodo</i>	1000x1000 mm
DIN 51130	R9
DIN 51097	A
ANSI A137.1 (DCOF)	≥ 0,42*

\* Guaranteed if requested at the time of ordering | *Garantito su richiesta in fase d'ordine |  
Garanti sur demande au moment de la commande | auf Anfrage in der Bestellphase garantiert | Garantizado por encargo durante la fase de pedido*

## Pendulum

Norm-Method		
<i>Norma-Metodo   Norme-Méthode   Norm-Methode   Norma-Metodo</i>		
Spanish test	UNE-ENV 12633:2003	on demand
English test	BS 7976-2:2002 PENDULUM TEST	on demand
Australian test	AS/NZS 4586	on demand

### ♦ FULL SIZE

Untrimmed end product. | *Lastra formata "uscita forno" quindi non rifilata. |  
Produit fini non coupe | Plattenformat nicht rektifiziert | Tabla formata "salida de horno" y, por lo tanto, no recortada.*

Pictures colours and features have to be considered indicative. | *Les teintes et les caractéristiques des images sont uniquement à titre indicatif |  
Die gezeigten Farben und Muster sind zureichend und nicht verbindlich | Los colores y las características de las imágenes deben considerarse solamente indicativas*